光源
Light Source

Spectral Products



ASBN-D130/ASBN-230 氖燈
Deep UV Deuterium Light Source Assembly

Features

- Provides maximum possible illumination
- Contains 1" quartz doublet assembly for optimum coupling
- Assures maximum stability and lifetime of lamp

Specifications

Lamp	
Type	Deuterium with fused silica jacket, mounted and pre-aligned.
Power input	30 Watt(nominal)
Lamp current	300 ± 30 mA DC
Average Life	1000 hours(nominal)
Lamp Housing	1" quartz doublet (f#/1,1X) collection lens. Convection cooled.
Dimension	6" x 5" x 10"
Power supply	Power input: 115 vac, 50/60 Hz, 32 amps, 230 vac, 50/60 Hz, 1 amp, optional
Power input	Constant current dc, 60-120vdc selectable, 300mA DC Regulation" + 10mA
Stability	100 ppm/°C
Operating Temperature	5-35°C
Warranty	One year
Option	Spare lamp(mounted and pre-aligned), specify SM, FC, ST, CL or SC for specific fiber couplers
Ordering information	
ASBN-D130-(F/M)	Single deep UV Deuterium
ASBN-D230-(F/M)	Double deep UV Deuterium

F: Fiber Coupling M: Monochromator f/# matching

方全有限公司
Rapitech Enterprise Co.,Ltd.
244 新北市林口區仁愛路二段309號10樓
Tel：886-2-2608-8096(台北) / Tel：86-21-6248-3333(上海) / Fax：886-2-2608-8092
E-mail：sales@rapi-tech.com.tw www.rapi-tech.com